




114.4270

Assembly Gloves

Full nitrile microfoam coating, unlined



- High durability, dexterity and tactile sensitivity.
- Resistant to contact heat up to 100°C for 15 s.
- Water and oil repellent.
- Sanitized® treated to prevent bacteria growth and promote freshness.

Standards and **Approvals**



EN 420:2003 + A1:2009





EN 388:2016





Suitable for:

Light and medium fabrication | General assembly | Automotive manufacturing | Motor mechanics for handling hot parts.







Oil Repellent

Precision

Water Repellent

CATEGORY:
All-round Gloves
Extreme-Fit Assembly Gloves

INDUSTRY:
Agriculture
Building and Construction
Logistics and Warehousing
Maintenance
Oil, Gas and Mining

	ANDARDS AND PROVALS:	
EN 4	420:2003 + A1:2009	
EN	407:2004	
EN :	388:2003	
EN :	388:2016	
CE (Cat.II	

PROTECTION AND **RESISTANCE:** Abrasion Resistant Oil Repellent Water Repellent

FEATURES AND PROPERTIES:

Precision

PRODUCT DETAILS

Liner material : Nylon Size : 8, 7 Coating material : Nitrile Length: 23-26 cm Fully coated Color: Yellow Coating type : Grip: Dry Glove fit : Tight fit

Sales Units Per Bundle: 12

PACKING / TRANSPORT

Sales Units Per Outer Case: 144